This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RESIN PRO SRL EPOXYTABLE TEN PART B

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: EPOXYTABLE TEN PART B

CAS: 9046-10-0 EC: 618-561-0 Index: Non-applicable

REACH: 01-2119557899-12-XXXX

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: The product is ideal for all users, both private and industrial, and for all hobby and professional uses

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

RESIN PRO SRL Via 25 Aprile z.i. snc 19021 Arcola (SP) - Liguria - Italy

Phone: +39 0187 955108 info@resinpro.it http://www.resinpro.it

1.4 Emergency telephone number: NHS Direct in England or Wales 0845 46 47

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Dam. 1: Serious eye damage, Category 1, H318 Skin Corr. 1C: Skin corrosion, Category 1C, H314

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.

Precautionary statements:

P102: Keep out of reach of children. - P103: Read label before use - P404: Store in a closed container. - P405: Store locked up

P264: Wash thoroughly after handling.

 $P280: We ar protective \ gloves/face \ protection/protective \ clothing/protective \ footwear.$

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

 $P303 + P361 + P353: IF\ ON\ SKIN\ (or\ hair): Take\ offinmediately\ all\ contaminated\ clothing.\ Rinse\ skin\ with\ water\ or\ shower.$

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a poison center/doctor.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Date of compilation: 07/04/2017 Revised: 29/02/2024 Version: 6 (Replaced 5) Page 1/11

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RESIN PRO SRL EPOXYTABLE TEN PART B

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Chemical description: Solution composed of amines

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification	Chemical name/Classification			Concentration
CAS:		Poly[oxy(methyl-1,2-et	hanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-	Self-classified	
EC: Index: REACH	618-561-0 Non-applicable : 01-2119557899-12- XXXX	Regulation 1272/2008	Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Corr. 1C: H314 - Danger		100 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

3.2 Mixture:

Non-applicable

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

By inhalation

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and also risk damage to the respiratory system through inhalation. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RESIN PRO SRL EPOXYTABLE TEN PART B

SECTION 5: FIREFIGHTING MEASURES (continued)

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

 $\hbox{ D.- Technical recommendations to prevent environmental risks}$

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 15 °C

Maximum Temp.: 35 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RESIN PRO SRL EPOXYTABLE TEN PART B

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

		Short ex	kposure	Long ex	posure
Identification		Systemic	Local	Systemic	Local
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 9046-10-0	Dermal	Non-applicable	Non-applicable	2,5 mg/kg	Non-applicable
EC: 618-561-0	Inhalation	Non-applicable	Non-applicable	10,58 mg/m ³	Non-applicable

DNEL (General population):

Non-applicable

PNEC:

Identification				
Poly[oxy(methyl-1,2-ethanediyl)], a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-	STP	7,5 mg/L	Fresh water	0,015 mg/L
CAS: 9046-10-0	Soil	0,018 mg/kg	Marine water	0,014 mg/L
EC: 618-561-0	Intermittent	0,15 mg/L	Sediment (Fresh water)	0,132 mg/kg
	Oral	0,00693 g/kg	Sediment (Marine water)	0,125 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)	CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CATII	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks	CAT III	EN 13034:2005+A1:2009 EN 168:2002 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk	CAT III	EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

Date of compilation: 07/04/2017 Revised: 29/02/2024 Version: 6 (Replaced 5) Page 4/11

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RESIN PRO SRL EPOXYTABLE TEN PART B

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 0% weight V.O.C. density at $20\,^{\circ}$ C: $0\ kg/m^3\ (0\ g/L)$ Average carbon number: Non-applicable Average molecular weight: Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Colourless

Odour:

Characteristic

Odour threshold:

Non-applicable *

Volatility:

Boiling point at atmospheric pressure: 208 °C

Vapour pressure at 20 °C:

Vapour pressure at 50 °C:

Non-applicable *

Evaporation rate at 20 °C:

Non-applicable *

Product description:

Density at 20 °C: 1100 kg/m³

Relative density at 20 °C: 1,1

Dynamic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 20 °C: $5.57 \text{ mm}^2/\text{s}$ Kinematic viscosity at 40 °C: Non-applicable * Concentration: Non-applicable * pH: Non-applicable * Non-applicable * Vapour density at 20 °C: Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable *

Flammability:

 * Not relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 07/04/2017 Revised: 29/02/2024 Version: 6 (Replaced 5) Page 5/11

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RESIN PRO SRL EPOXYTABLE TEN PART B

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Flash Point: 98 ºC

Flammability (solid, gas): Non-applicable *

Autoignition temperature: 358 °C

Lower flammability limit: Non-applicable *
Upper flammability limit: Non-applicable *

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable

Non-applicable *

Non-applicable *

Non-applicable *

components:

Other safety characteristics:

Surface tension at 20 $^{\circ}$ C: Non-applicable * Refraction index: Non-applicable * *Non-applicable *

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

Avoid overheating. Avoid all sources of ignition.

Avoid non-intentional contacts with epoxy costituents/acids. May produce an exothermic reaction, forming phenolic derivates, marbon monoxide and water.

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Avoid alkalis or strong bases

Other information:

Air. Oxidizing materials. Metals

10.6 Hazardous decomposition products:

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released, ammonia. Nitrogen oxide may react with water vapor to form corrosive nitric acid.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

Dangerous health implications:

Date of compilation: 07/04/2017 Revised: 29/02/2024 Version: 6 (Replaced 5) **Page 6/11**

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RESIN PRO SRL EPOXYTABLE TEN PART B

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.

B- Inhalation (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
 - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

 IARC: Non-applicable
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Product-specific toxicological information:

	Genus	
LD50 oral	2885,3 mg/kg	Rat
LD50 dermal 2979,7 mg/kg		Rabbit

Specific toxicology information on the substances:

Identification	Acut	e toxicity	Genus
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-	LD50 oral	2885,3 mg/kg	Rat
CAS: 9046-10-0	LD50 dermal	2979,7 mg/kg	Rabbit
EC: 618-561-0	LC50 inhalation	Non-applicable	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RESIN PRO SRL EPOXYTABLE TEN PART B

SECTION 12: ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Product-specific aquatic toxicity:

Acute toxicity		Species	Genus
LC50	772,14 mg/L (96 h)	Non-applicable	Fish
EC50	80 mg/L (48 h)	Non-applicable	Crustacean
EC50	15 mg/L (72 h)	Non-applicable	Algae

Substance-specific aquatic toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Poly[oxy(methyl-1,2-ethanediyl)], a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-	LC50	772,14 mg/L (96 h)	N/A	Fish
CAS: 9046-10-0	EC50	80 mg/L (48 h)	Daphnia magna	Crustacean
EC: 618-561-0	EC50	15 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-	BOD5	Non-applicable	Concentration	17.6 mg/L
CAS: 9046-10-0	COD	Non-applicable	Period	28 days
EC: 618-561-0	BOD5/COD	Non-applicable	% Biodegradable	0 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-	BCF	
CAS: 9046-10-0	Pow Log	1.34
EC: 618-561-0	Potential	

12.4 Mobility in soil:

Not available

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Hazardous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP8 Corrosive

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

RESIN PRO SRL EPOXYTABLE TEN PART B

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



14.1 UN number or ID number: UN2735
 14.2 UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-)

14.3Transport hazard class(es):8Labels:814.4Packing group:II14.5Environmental hazards:No

14.6 Special precautions for user

Special regulations: 274
Tunnel restriction code: E

Physico-Chemical properties: see section 9 Limited quantities: 1 L

14.7 Maritime transport in bulk according to IMO instruments:

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



14.1 UN number or ID number: UN2735
 14.2 UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-)

14.3 Transport hazard class(es): 8 Labels: 8

14.4Packing group:II14.5Marine pollutant:No

4.6 Special precautions for user

Special regulations:274EmS Codes:F-A, S-BPhysico-Chemical properties:see section 9Limited quantities:1 LSegregation group:SGG18

14.7 Maritime transport in bulk Non-applicable **according to IMO instruments**:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:



14.1 UN number or ID number: UN2735

4.2 UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-)

14.3 Transport hazard class(es): 8 Labels: 8

14.4 Packing group: II **14.5 Environmental hazards:** No

14.6 Special precautions for user

Physico-Chemical properties: see section 9 **14.7** Maritime transport in bulk according to IMO instruments:

SECTION 15: REGULATORY INFORMATION

Date of compilation: 07/04/2017 Revised: 29/02/2024 Version: 6 (Replaced 5) Page 9/11

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RESIN PRO SRL EPOXYTABLE TEN PART B

SECTION 15: REGULATORY INFORMATION (continued)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Texts of the legislative phrases mentioned in section 2:

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

 ${\bf Abbreviations\ and\ acronyms:}$

- CONTINUED ON NEXT PAGE
Date of compilation: 07/04/2017 Revised: 29/02/2024 Version: 6 (Replaced 5) Page 10/11

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RESIN PRO SRL EPOXYTABLE TEN PART B

SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor

LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET
Date of compilation: 07/04/2017 Revised: 29/02/2024 Version: 6 (Replaced 5) Page 11/11